



Product Number	Bearing Type	Bore Dia (d)	Outer Dia (D)	Width (B)	Dynamic Load Rating (Cr) (kN)	Static Load Rating (Cor) (kN)
5200	Open	10 mm	30mm	14.287mm	7.15	3.9
5200zz	Shielded	10 mm	30mm	14.287mm	7.15	3.9
5200-2RS	Sealed	10 mm	30mm	14.287mm	7.15	3.9
5201	Open	12 mm	32mm	15.875mm	10.6	5.85
5201zz	Shielded	12 mm	32mm	15.875mm	10.6	5.85
5201-2RS	Sealed	12 mm	32mm	15.875mm	10.6	5.85
5202	Open	15 mm	35mm	15.875mm	11.7	6.95
5202zz	Shielded	15 mm	35mm	15.875mm	11.7	6.95
5202-2RS	Sealed	15 mm	35mm	15.875mm	11.7	6.95
5203	Open	17 mm	40mm	17.462mm	14.8	9

5203zz	Shielded	17 mm	40mm	17.462mm	14.8	9
5203-2RS	Sealed	17 mm	40mm	17.462mm	14.8	9
5204	Open	20 mm	47mm	20.638mm	19.5	12.2
5204zz	Shielded	20 mm	47mm	20.638mm	19.5	12.2
5204-2RS	Sealed	20 mm	47mm	20.638mm	19.5	12.2
5205	Open	25 mm	52mm	20.638mm	21.2	14.6
5205zz	Shielded	25 mm	52mm	20.638mm	21.2	14.6
5205-2RS	Sealed	25 mm	52mm	20.638mm	21.2	14.6
5206	Open	30 mm	62mm	23.812mm	29.6	21.2
5206zz	Shielded	30 mm	62mm	23.812mm	29.6	21.2
5206-2RS	Sealed	30 mm	62mm	23.812mm	29.6	21.2
5207	Open	35 mm	72mm	26.990mm	37.7	27.5
5207zz	Shielded	35 mm	72mm	26.990mm	37.7	27.5
5207-2RS	Sealed	35 mm	72mm	26.990mm	37.7	27.5
5208	Open	40 mm	80mm	30.163mm	44.9	34
5208zz	Shielded	40 mm	80mm	30.163mm	44.9	34
5208-2RS	Sealed	40 mm	80mm	30.163mm	44.9	34
5209	Open	45 mm	85mm	30.163mm	48.8	39
5209zz	Shielded	45 mm	85mm	30.163mm	48.8	39
5209-2RS	Sealed	45 mm	85mm	30.163mm	48.8	39
5210	Open	50 mm	90mm	30.163mm	48.8	39
5210zz	Shielded	50 mm	90mm	30.163mm	48.8	39
5210-2RS	Sealed	50 mm	90mm	30.163mm	48.8	39
5211	Open	55 mm	100mm	33.338mm	57.2	47.5
5211zz	Shielded	55 mm	100mm	33.338mm	57.2	47.5
5211-2RS	Sealed	55 mm	100mm	33.338mm	57.2	47.5
5212	Open	60 mm	110mm	36.513mm	70.2	58.5
5212zz	Shielded	60 mm	110mm	36.513mm	70.2	58.5
5212-2RS	Sealed	60 mm	110mm	36.513mm	70.2	58.5
5213	Open	65 mm	120mm	38.100mm	80.6	73.5
5213zz	Shielded	65 mm	120mm	38.100mm	80.6	73.5
5213-2RS	Sealed	65 mm	120mm	38.100mm	80.6	73.5
5214	Open	70 mm	125mm	39.688mm	88.4	80
5214zz	Shielded	70 mm	125mm	39.688mm	88.4	80
5214-2RS	Sealed	70 mm	125mm	39.688mm	88.4	80
5215	Open	75 mm	130mm	41.275mm	95.6	88
5215zz	Shielded	75 mm	130mm	41.275mm	95.6	88

5215-2RS	Sealed	75 mm	130mm	41.275mm	95.6	88
5216	Open	80 mm	140mm	44.450mm	106	95
5216zz	Shielded	80 mm	140mm	44.450mm	106	95
5216-2RS	Sealed	80 mm	140mm	44.450mm	106	95
5217	Open	85 mm	150mm	49.213mm	124	110
5217zz	Shielded	85 mm	150mm	49.213mm	124	110
5217-2RS	Sealed	85 mm	150mm	49.213mm	124	110
5218	Open	90 mm	160mm	52.388mm	130	120
5218zz	Shielded	90 mm	160mm	52.388mm	130	120
5218-2RS	Sealed	90 mm	160mm	52.388mm	130	120
5219	Open	95 mm	170mm	55.563mm	165	153
5219zz	Shielded	95 mm	170mm	55.563mm	165	153
5219-2RS	Sealed	95 mm	170mm	55.563mm	165	153
5220	Open	100 mm	180mm	60.325mm	186	173
5220zz	Shielded	100 mm	180mm	60.325mm	186	173
5220-2RS	Sealed	100 mm	180mm	60.325mm	186	173